



DMXB - DynaMax X Bracket
Used to connect all cross tees together for rigid connection

DMIB - DynaMax I Bracket
Used to splice together main beams ends

Turnbuckles and threaded rods are used to connect to X-brackets to create a structural support for the grid

DMTB - DynaMax T Bracket
Used to connect main beams and cross-tees to the perimeter extrusion

DMLB - DynaMax L Bracket
Used to connect perimeter extrusion corners together.

These drawings show typical conditions in which the Armstrong product depicted is installed. They are not a substitute for an architect's or engineer's plan and do not reflect the unique requirements of local building codes, laws, statutes, ordinances, rules and regulations (Legal Requirements) that may be applicable for a particular installation.

Armstrong does not warrant, and assumes no liability for the accuracy or completeness of the drawings for a particular installation or their fitness for a particular purpose. The user is advised to consult with a duly licensed architect or engineer in the particular locale of the installation to assure compliance with all Legal Requirements.

Armstrong is not licensed to provide professional architecture or engineering design services.

PROJECT NAME:

**DYNAMAX PLUS
LADDER WITH CABLE TRAY**

DWG. NO. **DETAIL**

REV: .

DATE: .

DATE: **5/15/2023**

SCALE: -

DESC.: .

DRAWN BY: **RSK**

CHK BY: .